

Lamino

Laminatboden der Extraklasse.


Laminate floor to click with HDF core board.



Technical Data	Lamino Trend	Lamino Style	Lamino Long
Plank format	1.285 x 192 x 8,0 mm	1.285 x 192 x 8,0 mm	2.000 x 242 x 10,0 mm
Packaging unit	9 planks/2,22 m ²	9 planks/2,22 m ²	5 planks/2,42 m ²
Palette content	52 cartons/115,46 m ²	52 cartons/115,46 m ²	30 cartons/72,60 m ²
Wear layer	Melamine decorative film with overlay		
Carrier board	8,0 mm HDF		10,0 mm HDF
Underlay	-		
Edge processing	-	V-Gap	V-Gap
Laying method	Twincllic Technik	1cllic 2go pure Technik	1cllic 2go pure Technik
Testing Values			
Abraison resistance (EN 13329)	Ac 4		
Resilient flooring classification (EN 685)	23/32		
Determination of burning behaviour (EN 13501-1)	Cfl-s1 • Does not release toxic gas during combustion		
Moisture proof	No		
Stain resistance (EN 13329)	Level 5		
Formaldehyde emission	Within the E1 standard		
Suitable for underfloor heating	Yes, in conjunction with PE film as a vapor barrier Yes (Hot water underfloor heating)		
Slip retardant (EN 13893)	DS		
Light fastness (EN 13329)	6		
Residual indentation	< 0,05 mm		
Impact resistance big ball	≥ 750 mm		
Suitable for caster chairs (EN 425)	Yes, with casters type W		
Thermal conductivity (DIN-EN 12667)	0,073 m ² x K/W	0,073 m ² x K/W	0,091 m ² x K/W
Disposal	Household waste		



MADE IN GERMANY



Regularly Emission tested under test chamber-conditions according to DIN ISO 16000-9 and DIN EN 717-1 i.A.

