



Linoplus[®]
Extra robust above. Extra soft below.



The robust linoleum floor with the extra strong Cork impact sound insulation.

| Technical Data | |
|--|---|
| Plank format | 900 x 300 x 11 mm |
| Packaging unit | 6 planks/1,62 m ² |
| Palette content | 60 cartons/97,20 m ² |
| Surface | Acrylic polish treatment, marbled look |
| Top layer | 2,0 mm double layer linoleum |
| Carrier board | 6,0 mm HDF |
| Underlay | 3,0 mm Pressed cork impact sound insulation |
| Edge processing | 4-side flat |
| Laying method | Glueless UNICLIC technique |
| Testing Values | |
| Electrostatic propensity (EN 1815) | < 2 kV |
| Resilient flooring classification (EN 685) | 23/32 |
| Determination of burning behaviour (EN-ISO 9239-1) | Cfl-s1 • Does not release toxic gas during combustion |
| Resistance to chemicals (EN 423) | Resistant to diluted acids, oils, fats, etc. |
| Moisture proof | No |
| Mass per unit area (EN 430) | 8.700 g/m ² |
| Suitable for underfloor heating | Yes (Hot water underfloor heating) |
| Residual indentation (EN 433) | 0,12 mm |
| Slip retardant (DIN 51130 • EN 13893) | DIN = R 9 • EN = DS > 0,30 |
| Suitable for caster chairs (EN 425 • EN 12529) | Yes, with casters type W |
| Impact sound reduction (DIN 52210-030 E1-T-PFLD) | 17 dB |
| Thermal conductivity (DIN-EN 52612-Teil 1) | 0,103 m ² x K/W |
| Resistance to stubbed and burning cigarettes (EN 1399) | Yes |
| Disposal | Household waste or Second Life |



MADE IN EUROPE