

# Vinyl Living Rigid

**Design vinyl finished floor with rigid polymer core board.  
Suitable for damp rooms.**

Technical Data	
Plank format	1.220 x 180 x 4,5 mm
Packaging unit	10 planks/2,20 m <sup>2</sup>
Palette content	45 cartons/99,0 m <sup>2</sup>
Wear layer	0,30 mm transparent, structured wear layer
Top layer	0,10 mm vinyl decorative foil
Carrier board	3,50 mm rigid polymer (plasticizer free)
Underlay	0,6 mm IXPE impact sound underlay
Edge processing	4-sided super micro bevel
Laying method	Glueless UNICLIC technique
Testing Values	
Resilient flooring classification (EN 685)	23/32
Determination of burning behaviour (EN 13501-1)	Bfl-s1 • Does not release toxic gas during combustion
Moisture proof	Yes (glued down)
Mass per unit area (EN 430)	7.900 g/m <sup>2</sup>
Suitable for underfloor heating	Yes (Hot water underfloor heating)
Light fastness (EN ISO 105-B02)	> 6
Residual indentation (EN 433)	0,03 mm
Slip retardant (DIN 51130 • EN 13893)	DIN = R 10/DS
Suitable for caster chairs (EN 425 • ISO 4918)	Yes, with casters type W
Impact sound reduction (ISO 10140-3)	17 dB
Thermal conductivity (DIN-EN 12524)	0,036 m <sup>2</sup> x K/W
Resistance to stubbed and burning cigarettes (EN 1399)	Yes
Disposal	Household waste

