

Vinylanfixx Rigid

Komfort Rigid-Planke mit Trittschall.



Design vinyl finished floor with 10 or 12-layer vinyl core board including 2-fold glass fiber fabric and integrated impact sound insulation.

Technical Data		Vinylanfixx Rigid 30	Vinylanfixx Rigid 55
Plank format	Stone	-	610 x 303 x 6,0 mm
	Wood	1.318 x 189 x 5,0 mm	1.318 x 189 x 6,0 mm
Packaging unit	Stone	-	10 plank/1,85 m ²
	Wood	10 plank/2,49 m ²	8 plank/1,99 m ²
Palette content	Stone	-	36 cartons/66,60 m ²
	Wood	48 cartons/119,52 m ²	44 cartons/87,56 m ²
Wear layer		0,30 mm + 2-fold PU finish and subsequent embossing	0,55 mm + 2-fold PU finish and subsequent embossing
Carrier board		3,7 mm solid virgin Vinyl	4,45 mm solid virgin Vinyl
Underlay		1,0 mm PE impact sound underlay	
Edge processing		4-sided micro bevel	4-sided bevel
Laying method		floating - click system	
Testing Values			
Resilient flooring classification (DIN EN 16511)	23/32		23/33
Determination of burning behaviour	Bfl-s1 (DIN EN 9239-1) • Does not release toxic gas during combustion		
Moisture proof	Yes (glued down)		
Mass per unit area (DIN EN ISO 23997)	7.000 g/m ²		8.668 g/m ²
Suitable for underfloor heating	Yes (Hot water underfloor heating)		
Light fastness (ISO 105-B02)	> 6		
Residual indentation (DIN EN ISO 24343-1)	< 0,1 mm		
Slip retardant (DIN 51130 • EN 13893)	R 10/DS		
Suitable for caster chairs (DIN EN 425)	Yes, with casters type W		
Impact sound reduction (DIN EN ISO 717-2)	19 dB		21 dB
Thermal conductivity (DIN EN 12524)	0,025 m ² x K/W		
Resistance to stubbed and burning cigarettes (DIN EN 1399)	Yes		
Disposal	Household waste		

