

ZIRO-KORK

Colorparkett •

Colored parquet for gluing to the subsurface.
Ecological, healthy living, but also hard-wearing floor covering.

Technical Data				
Plank format	600 x 300 x 4 mm	600 x 300 x 6 mm	600 x 450 x 5 mm	600 x 150 x 4 mm
Packaging unit	55 pieces/9,90 m ²	33 pieces/5,94 m ²	30 pieces/8,10 m ²	110 pieces/9,90 m ²
Palette content	24 cartons/237,60 m ²	24 cartons/142,56 m ²	24 cartons/194,40 m ²	24 cartons/237,60 m ²
Top layer (natural cork)	4 mm	6 mm	5 mm	4 mm
Coloring	Hard wax oil / PU varnish			
Binder	Polyurethane			
Laying method	To glue			
Testing Values				
Resilient flooring classification	23/31 (EN 685)			
Determination of burning behaviour	B 2 (EN-ISO 9239-1) • Does not release toxic gas during combustion			
Vapor diffusion resistance	Decor „Duro HD“: 2.458 μ			
Moisture proof	Yes			
Mass per unit area (EN 430)	Decors „massiv“: +/- 480 g/m ² Decor „Duro HD“: +/- 520 g/m ² Decors „edelfurniert“: +/- 520 g/m ²			
Suitable for underfloor heating	Yes (Hot water underfloor heating)			
Residual indentation (EN 433)	Decors „massiv“: 0,34 mm Decor „Duro HD“: 0,19 mm Decore „edelfurniert“: 0,34 mm			
SD-Value (DIN 52615)	Decor „Duro HD“: 9,83 mm			
Impact sound reduction (DIN 52210-030 E1-T-PFLD)	13 - 16 dB			
Thermal conductivity (DIN-EN 51612-Teil 1)	0,050 m ² x K/W			
Disposal	Household waste or Second Life			