

Corelan[®]plus

The cork design floor

Cork floor to click with HDF core board



Technical Data	
Plank format	1.200 x 210 x 10,5 mm
Packaging unit	6 planks/1,512 m ²
Palette content	60 cartons/90,72 m ²
Surface	4-fold PUR-High Resistant sealing, high-resolution decor print
Top layer	3,0 mm natural cork
Carrier board	6,0 mm HDF
Underlay	1,5 mm Pressed cork impact sound insulation
Binder	Polyurethane
Edge processing	4-sided super micro bevel
Laying method	Glueless UNICLIC technique
Testing Values	
Resilient flooring classification (EN 685)	23/31
Determination of burning behaviour	Cfl-s1 (EN-ISO 9239-1) • Does not release toxic gas during combustion
Moisture proof	No
Mass per unit area (EN 430)	8.400 g/m ²
Suitable for underfloor heating	Yes (Hot water underfloor heating)
Light fastness (EN 105-B02)	6
Residual indentation (EN 433)	0,14 mm
Slip retardant (DIN 51130 • EN 13893)	R 9 DS
Impact sound reduction (EN 140)	17 dB
Thermal conductivity (DIN-EN 52612-Teil 1)	0,115 m ² x K/W
Disposal	Household waste or Second Life